

## KOREAN PATENT ABSTRACT (KR)

## **PUBLICATION**

(65) Publication No.: 1996-035821

(43) Publication Date: 28 October 1996

(21) Application No.: 1995-006557

(22) Application Date: 27 March 1995

(51) IPC Code: H01L 21/28

(71) Applicant:

Hyundai Electronics Co., Ltd. 136-1 Amiri san, Bubal-eup, Icheon-city, Kyunggi-do, Korea

(72) Inventor:

PARK, SANG HOON

(54) Title of the Invention:

Method of forming contact hole

## Abstract:

The present invention relates to a method of forming a contact hole of a semiconductor device including forming a predetermine metal layer pattern 12. In particular, the method includes forming a first dielectric layer 13 on a predetermined structure, forming a spin-on-glass (SOG) layer 14 on the structure, implanting predetermined ions into the SOG layer 14 in order to suppress emission of OH radicals and performing a first curing process, forming a first curing process, forming a second dielectric layer 15 on the SOG layer 14, and removing the second dielectric layer 15, the SOG layer 14, and the first dielectric layer 13 in a predetermined region. Accordingly, it is possible to prevent OH radicals from discharging from the SOG layer 14 and thus prevent holes or a naturally oxidized layer from forming between metal layers. Furthermore, it is possible to enhance semiconductor device yields and reliability.